

TEGRASEAL MASTIC  
CENTERED OVER EDGE

4"

SAND SLURRY PROTECTION  
SLAB

BENTONITE SIDE OF  
TEGRATITE PLUS  
FACING UP

COMPACTED BASE OR SAND  
SLURRY UNDER SLAB

SECURE WITH PINS AND  
WASHERS OR WIDE CROWN  
BOX STAPLES AT THE SEAMS  
AS NEEDED. SEAMS AND  
FASTENER HEADS ARE TO  
BE COVERED WITH  
CURETITE

SOIL OR COMPACTED  
GRANULAR BASE

**NOTES:**

1. SAND SLURRY PROTECTION SLAB AND MUD SLAB ARE RECOMMENDED FOR HEAVILY REINFORCED SLABS GREATER THAN 6" THICK THAT ARE TO BE PLACED ON DAMP OR UNSTABLE EARTH.
2. PRODUCTS REQUIRE A MIN. OF 24 PSF OF COMPACTION / CONFINEMENT IN ORDER TO FUNCTION AS DESIGNED.
3. WHEN POURING CONCRETE, POUR EITHER DIRECTLY ON TOP OF THE SEAM OR TOWARDS THE CLOSED EDGE OF THE SEAM SO AS NOT TO DISLodge THE SEAM AND / OR ALLOW CONCRETE BETWEEN THE LAPPED SEAM.



Tel: 952-888-1816  
Web: [www.tegraseal.com](http://www.tegraseal.com)

**SEAM APPLICATION FOR MUDSLAB / SOIL**

Designed	JF	2023
Drawn	TB	2023
Approved	JF	2023
FILE NAME: 0204-60		
SCALE: N.T.S.		